

Tender book for casing pipes order
Seamless steel casing acc.to API 5C.T range - 3 as following

Item	O.D	Grade	Weight Lb/ft	group	Thread type	coupling	QTY
1	20"	K55	94	1	B.T.C	Regular	1000 meters
1-1	Coupling for item 1						100 Piece
2	9 5/8"	L - 80	43.5	2TYPE1	B.T.C	Regular	4000 meters
3	9 5/8"	L - 80	47	2TYPE1	B.T.C	Regular	4000 meters
4	5"	Q - 125	18	4	B.T.C	Regular	1000 meters
5	4 1/2"	L - 80	13.5	2 TYPE 1	B.T.C	Regular	1000 meters

Remarks

- 1- Valid API -5CT certificate should be enclosed with the offer . includes the following (the manufacturer of casing plain end ,manufacturer of casing threaded and coupled, processor of casing plain end, processor of casing threaded and coupled)
- 2- if the bidder has more than one manufacturer , a valid API -5CT certificate for every manufacture concerns his item(coupling , connection thread , body)
should be submitted
- 3- Mill test certificate for material and pipes will be enclosed with the shipment including (int hydrostatic pressure ,mechanical properties ,chemical composition, heat treatment, thickness,...) for pipes
- 4-Pipe will be supplied with internal and external closed end protectors.
- 5- pipe should be coated with varnish coating for long time storage to protect them from the rust and corrosion
- 6- Clearly marketing should be typed on the pipes body including(casing manufacturing, ,origin country , OD ,grade, weight lp/ft, heat treatment, pipe long , type of thread , and all other specification Acc to API- 5CT
- 7-The make -up triangle shall be stamped on the outside of each pipe on the both ends with a white band to assist in locating the triangle
- 8-The color of couplings and number of bands shall be placed on the pipes
- 9- Analyzing certificate for metal from manufacture should be submitted during Purchase
- 10- origin country and the manufacturer should be mentioned

11- The materials should be new , not renewed

12-Certificate issued by neutral international inspection company approved by the Syrian petroleum Company stating That the materials are conforming with specifications and API standards and tests specified in tender book with the shipment

13-The maximum number of manufacturers allowed is only two for all materials
